

PRODUCT DATA SHEET

FPC-9: Primed Hardboard

SPECIFICATIONS

Max Size: Singles: 4'0" x 10'0", Pairs available

Transoms: Available

Thickness: 1-3/4", 1-3/8" & 2-1/4"

Core: Particleboard which complies with ANSI A208.1 1-LD2 or 1-LD1.

Door Facing: Primed Hardboard

Stiles: Mill option

Rails: 2-1/4" min. (before trim) mill option

Adhesives: Door assembly – Type I

Lites*: Metal vision frames open for 1/4" wired glass or 3/16" Firelite NT glass. Max visible glass 1296 sq in; max width 36", max length 54" Wood lip, wood flush or Metal Vision Panel.

Blocking: Top rail, bottom rail, stiles and special blocking can be specified to meet specialized hardware requirements.

Warranty: Five Lakes doors are warranted for interior use only. One year (standard), 2 year and 5 year are repair, replace or refund only. Life of Installation Warranty with additional benefits available

Machining: Prefitting, beveling, lock and hinge mortise and other hardware preps available.

Fire Rating: 20-minute available
Neutral (standard) and Positive Pressure Category B**
Intertek Testing Service/Warnock Hersey international (ITS-WHI) 1-3/4" or 1-3/8" (single only)

*Minimum 5.5" from any edge of door including hardware cutouts, to meet labeling and warranty requirements.

**Contact Five Lakes for size restrictions

